



Furniture for people

# Specification sheet

## S 2000 Classic

The timeless basic range  
– complete and competent



Variations	Sub-frame	No. of compartments	Height	Compartment width	Depth
<b>Full height lockers</b>	Feet	1-5	1850 mm	300/400 mm	500 mm
	Plinth	1-5	1800 mm	300/400 mm	500 mm
	Bench In front	1-5	1850 mm	300/400 mm	815 mm
	Lowered bench underframe	1-5	1850 mm	300/400 mm	815 mm
	Bench underneath	1-5	2090 mm	300/400 mm	815 mm
<b>Lockers with pairs of doors</b>	Feet	2 or 4	1850 mm	2x300 / 2x400 mm	500 mm
	Plinth	2 or 4	1800 mm	2x300 / 2x400 mm	500 mm
	Bench in front	2 or 4	1850 mm	2x300 / 2x400 mm	815 mm
	Lowered bench underframe	2 or 4	1850 mm	2x300 / 2x400 mm	815 mm
	Bench underneath	2 or 4	2090 mm	2x300 / 2x400 mm	815 mm
<b>Lockers with one door over two compartments</b>	Feet	2 or 4	1850 mm	2x300 / 2x400 mm	500 mm
	Plinth	2 or 4	1800 mm	2x300 / 2x400 mm	500 mm
	Bench underneath	2 or 4	2090 mm	2x300 / 2x400 mm	815 mm
<b>Laundry, cleaning and storage lockers</b>	Feet	2	1850 mm	2x300 / 2x400 / 1x600 mm	500 mm
	Plinth	2	1800 mm	2x300 / 2x400 / 1x600 mm	500 mm
<b>Double-tier lockers</b>	Feet	2-4	1850 mm	300/400 mm	500 mm
	Plinth	2-4	1800 mm	300/400 mm	500 mm
	Bench underneath	2-4	2090 mm	300/400 mm	815 mm
<b>Assembled box lockers, 3-5 tiers</b>	Feet	1-4	1850 mm	300/400 mm	500 mm
	Plinth	1-4	1800 mm	300/400 mm	500 mm
<b>Z-lockers with fixed doors or folding-door mechanism</b>	Plinth	2 or 4	1820 mm	Total width: 420 /820 mm	510 mm
	Bench underneath	2 or 4	2090 mm	Total width: 420 /820 mm	825 mm

**Construction details:**

Carcass	Sturdy steel construction – material thickness 0,88 mm CVL – Classic Ventilation Concept Sub-frame options: With feet, with plinth or with bench 2 types of compartment width
Doors	Steel doors. Doors hinged right, borne on bolt hinges with vertical box reinforcements, louvers and stamped in label holder. Standard doorstop silencer. The Assembled box lockers have smooth doors.
Interior	Lockers: Slot-in hat shelf and wardrobe rail made of oval profile with 3 twist-proof sliding hooks for each compartment. Laundry, cleaning and storage lockers: Not adjustable shelves, some with hat shelf, coat rail and hooks.
Locks	Full height lockers and double-tier lockers are with turning bolt latch for padlock as standard. Assembled box lockers are with cylinder lock as standard.
Colors	C+P standard colors

**Options:**

Feet	Feet in plastic for improved corrosion protection. Height adjustable (10 mm)
Plinth	Steel plinth. Not height adjustable
Bench	3 types of lockers with bench: In front, with lowered bench underframe and with bench underneath. Bench slats made of beech as standard design, approx. 60 x 35 mm side-face, planed on all sides, rounded at the top, finished with clear varnish, with natural color differences. Plastic bench slats are available at no additional charge. Standard color of bench bases: Black gray RAL 7021. Bench height: 420 mm Bench depth: 315 mm Locker depth: 500/815 mm Shoe rack is available at additional charge.
Locks	Turning bolt latch for padlock, Cylinder lock with or without master key system Cylinder locks in moisture-proof design Coin locks Digilocks Mechanical combination lock Ask for other locking systems
Accessories	Number plates, plastic key rings, wristband for keys, padlocks, sloping top, additional interior fittings, top lockers, different kind of door finish

## Details and options:



### Special plastic feet for improved corrosion protection:

Classic feet are 150 mm high, made of sturdy plastic. They are available with standard floor gliders or additionally with height adjustment screws for easy leveling of the locker.



### Coat hangers:

With special attachment, made of hardwood varnished black.



### Door opening limiter 90°:

Made of sturdy round metal. Attached at the top to prevent impairment of locker use.



### Additional shelf:

Installation height approx. 250 mm. Cannot be height adjusted or retrofitted.



### Interior security compartment:

Instead of the hat compartment. With cylinder lock. Available for compartment widths of 300 and 400 mm.